Technical Data Sheet

CODE 65107

VORT-KRYO POLAR 12

Portable air conditioners






Certifications **C€** Œ

TECHNICAL AND PERFORMANCE DATA

Absorbed Current max (A)	6,3
Absorbed Power max (W)	1326
Compressor Type	Rotativo
Frequency (Hz)	50
Max ambient temperature for continuous operation (°C)	35
Min ambient temperature for continuous operation (°C)	18
Number of Phases (Ph)	1
Refrigerant Type	R-410A
Standard refrigerant charge (g)	570

voitage (v)	220-240
Weight (Kg)	29,5
Cooling Capacity (BTU/h)	11812
Cooling Capacity (W)	3462
Delivery max (m³/h)	460
EER (Energy Efficiency Ratio)	2,61
Sound power level Lw [dB(A)]	65
Sound pressure level Lp in free field [dB(A)] 1 m	57
Sound pressure level Lp in free field [dB(A)] 3 m	42.5 / 44 / 46

DIMENSIONS



Etichetta Energetica	NO
Size A (mm)	790
Size L (mm)	420
Size P (mm)	405

Technical Data Sheet

CODE 65107

VORT-KRYO POLAR 12

Portable air conditioners



DESCRIPTION

- Inner and outer cabinet components moulded from ABS thermoplastic resin.
- \bullet 4 operating modes: automatic, cooling, dehumidifying, ventilation.
- Class A appliance capable of two operating modes: air-air and waterair (adiabatic), the second of which guarantees superior cooling capacity and significantly greater energy efficiency of the product.
- No installation procedures necessary: the only requirement is to ensure that hot air can be ducted away from the climate-controlled room via the exhaust hose.
- \bullet Equipped with electronic controls and LCD display at the cabinet, and \quad o Foam board with a modern infrared remote control.
- Continuous internal drainage system automatically converts water of o Round plug condensation into vapour, which is then exhausted outdoors.
- Programmable timer: allows selection of ON/OFF cycles at intervals of o Infrared remote control
- 1 hour over a period of 12 hours.

- \bullet "SLEEP": optimizes energy consumption at night; the set temperature is increased by 1 $^{\circ}\text{C}$ every two hours.
- Washable dust filter
- · Activated carbon filter serving to remove unpleasant smells.
- It contains fluorinated greenhouse gases.
- Hermetically sealed equipment.
- · Accessories supplied:
- o Round adapter;
- o Hot air exhaust hose
- o Foam board with round hole
- o Condensate tank